

Uni-Vac (V-03)



Vacuum Conveying System

The **Uni-Vac** vacuum conveying system from **Hanningfield Process Systems** provides a safe, practical and dust-free method of conveying powder, granules and flakes without waste.

{xtypo_info}The **Uni-Vac V-03** is Hanningfield's smallest vacuum conveyor and is designed for applications where the throughput requirement is quite low. The capacity is 3 litres and the

throughput can reach 300 kgs/hr.{/xtypo_info}

<u>Vacuum conveying</u> provides cost-effective automation that improves production, reduces contamination and creates a clean and safer working environment. Powder spillage, airborne dust and the common problems associated with manual feeding are eliminated.

The conveyor is designed for applications with typical industry requirements. The handling of heavy drums, kegs, bags, etc. are all eliminated by using a **Uni-Vac** system.

Conveying offers various benefits for processing, such as increased productivity and a safer working environment. <u>Vacuum conveying</u> is the ideal solution for many powder processing applications in the pharmaceutical, food, chemical and allied industries.

Through conveying, a process can take advantage of improved output and a cleaner, safer working environment.

{faq inline/tabs}

Profile The Uni-Vac V-03 is Hanningfield's smalles offers many advantages Usin Maes an easy clean is connected to the Surface street and crevice free, the surface finish is to customer requirements. All connected to the Uni-Vac is designed and manufataments of the Uni-Vac is designed and manufataments.

Features •Easy clean design

- •Hygienic crevice free
- •Stainless steel construction (304 or 316)
- •No tools required for disassembly
- Remotely located controls
- •Flexible modular design
- •Mobile or static versions available

Benefits •High return on investment through increased productivity and lower productivity

- Improved working environment
- •Increased output and efficiency through automation
- •Improved dust free environment through containment
- Minimal risk of contamination
- Reduces product loss
- Increased process safety
- •Reduced operator fatigue
- •Easy to clean design for minimal operational downtime

Technical Specifications Throughput: Up to 300 kgs/hr

Volume: 3 litres

Material of Constructio6 tainless steel (304 or 316)

2/5

Height: 600mm
Diameter: 270mm

Pick-Up Method: Vacuum wand, IBC, sacktip station, feedbin, big bag, e

• Controls: Control panel can be attached or remotely located

Version: Mobile or static versions available
Explosion Protection: ATEX or Non-ATEX version available

Typical Applications •Unloading storage containers (IBCs, big bags etc.)

- •Fluid bed dryer unloading
- Mixer loading
- •IBC loading
- •Conveying powder through a conical screen mill for in-line milling
- •Conveying to a tablet compression machine
- •Conveying to a capsule filling machine

Gallery {gallery}univac03{/gallery}

{/faq}

{faq inline/sliders}

What is Pneumatic Powder Conveying?



Vacuum Powder Conveying known as

Pneumatic Powder Consequing hod of transferring pover

Benefits of Pneumatic Provedentation receipting in the larentance multiparty and the provedentation of transformation of transformation of the larentance multiparty and the larentance mu

For example, powder can be sucked directly from an IBC, into the conveyor, and then transferred from the Pneumatic Powder Conveyinge Contidution for being the province of the province of the conveyor, and then transferred from the province of the conveyor, and then transferred from the province of the conveyor, and then transferred from the province of the conveyor, and then transferred from the province of the conveyor and then transferred from the conveyor and then transferred from the province of the conveyor and then transferred from the conveyor and the conveyor an

{/faq}

Download Brochure:

{xtypo_download} T

Vacuum Conveying Systems (Uni-Vac Series) {/xtypo_download} Case Study:

{xtypo_download}

Vacuum Conveying {/xtypo_download}

